

## DIN EN 856 4SP

### SEMPERIT



**Hortum:**  
Sentetik kauçuk, hidrolik yağa uygun.

**Örgü Tipi:**  
Gergin 4 Çelik Spiral

**Çalışma Sıcaklığı:**  
-40°C / 100°C (max. 120°C)

| Nominal<br>Ø |      | İç<br>Ø | Sargı<br>Ø | Dış<br>Ø | Çalışma<br>Basıncı |      | Test<br>Basıncı | Patlama<br>Basıncı | Bükülme<br>Yarıçapı | Kütle |
|--------------|------|---------|------------|----------|--------------------|------|-----------------|--------------------|---------------------|-------|
| mm           | inch | mm      | mm         | mm       | bar                | psi  | bar             | bar                | mm                  | kg/m  |
| 10           | 3/8  | 9.9     | 17.7       | 21.0     | 445                | 6455 | 890             | 1780               | 180                 | 0.70  |
| 12           | 1/2  | 13.0    | 20.6       | 24.2     | 425                | 6465 | 850             | 1700               | 230                 | 0.85  |
| 16           | 5/8  | 16.4    | 24.2       | 27.9     | 350                | 5075 | 700             | 1400               | 250                 | 1.11  |
| 19           | 3/4  | 19.5    | 28.3       | 31.9     | 350                | 5075 | 700             | 1400               | 300                 | 1.41  |
| 25           | 1    | 26.0    | 35.1       | 39.1     | 320                | 4640 | 640             | 1280               | 340                 | 1.86  |